

# **ALL-NEW FORD FOCUS SPECIFICATIONS**

## PERFORMANCE AND ECONOMY

Focus 5-door					el consump /100 km (mp		Pe	erforman	ce
Petrol engines	Power PS	Wheel size	CO₂ g/km	Urban	Extra Urban	Combined	Max speed km/h (mph)	0-100 km/h (0-62 mph) sec	50-100 km/h (31-62 mph) sec*
1.0 EcoBoost 6-speed manual	85	16-inch	110	6.0 (47.1)	4.2 (67.2)	4.8 (58.8)	177 (110)	13.5	12.0
1.0 EcoBoost 6-speed	100	16-inch**	107	5.8 (48.7)	4.1 (68.9)	4.7 (60.1)	186	12.1	12.0
manual	100	17-inch	110	6.0 (47.1)	4.3 (65.7)	4.9 (57.6)	(116)	12.1	12.0
	105	16-inch	108	5.9 (47.9)	4.2 (67.2)	4.8 (58.8)			
1.0 EcoBoost 6-speed manual	125	17-inch	111	6.0 (47.1)	4.3 (65.7)	4.9 (57.6)	200 (124)	10.0	10.0
		18-inch	115	6.2 (45.6)	4.5 (62.8)	5.1 (55.4)	(127)		
		16-inch	126	7.1 (39.8)	4.7 (60.1)	5.6 (50.4)		11.1 N/A	
1.0 EcoBoost 8-speed automatic	125	17-inch	128	7.2 (39.2)	4.8 (58.8)	5.7 (49.5)	195 (121)		N/A
		18-inch	131	7.3 (38.7)	4.9 (57.6)	5.8 (48.7)	(121)		
		16-inch	121	6.9 (40.9)	4.5 (62.8)	5.3 (53.3)			
1.5 EcoBoost 6-speed manual	150	17-inch	123	6.9 (40.9)	4.6 (61.4)	5.4 (52.3)	210 (130)	8.8	8.6
mandar		18-inch	125	7.0 (40.3)	4.7 (60.1)	5.5 (51.4)	(100)		
		16-inch	133	7.6 (37.2)	4.9 (57.6)	5.9 (47.9)			
1.5 EcoBoost 8-speed automatic	150	17-inch	136	7.7 (36.7)	5.0 (56.5)	6.0 (47.1)	208 (129)	8.9	N/A
		18-inch	138	7.8 (36.2)	5.1 (55.4)	6.1 (46.3)	(120)		
1.5 EcoBoost 6-speed	182	17-inch	124	7.0 (40.3)	4.6 (61.4)	5.5 (51.4)	222	8.3	8.3
manual	102	18-inch	126	7.1 (39.8)	4.7 (60.1)	5.5 (51.4)	(138)	0.3	0.3

Focus 5-door					el consump /100 km (mp	P	Performance			
Diesel engines	Power PS	Wheel size	CO₂ g/km	Urban	Extra Urban	Combined	Max speed km/h (mph)	0-100 km/h (0-62 mph) sec	50-100 km/h (31-62 mph) sec*	
		16-inch**	91	3.8 (74.3)	3.3 (85.6)	3.5 (80.7)	400			
1.5 EcoBlue 6-speed manual	95	16-inch	92	3.8 (74.3)	3.4 (83.1)	3.5 (80.7)	183 (114)	11.4	10.9	
mandai		17-inch	95	3.9 (72.4)	3.5 (80.7)	3.6 (78.5)	()			
1.5 EcoBlue 6-speed	120	16-inch	94	4.0 (70.6)	3.4 (83.1)	3.6 (78.5)	196	10.0	10.4	
manual		17-inch	97	4.0 (70.6)	3.5 (80.7)	3.6 (78.5)	(122)			

		18-inch	100	4.1 (68.9)	3.6 (78.5)	3.7 (76.3)			
		16-inch	111	4.7 (60.1)	3.9 (72.4)	4.2 (67.2)	100		
1.5 EcoBlue 8-speed automatic	120	17-inch	113	4.8 (58.8)	4.0 (70.6)	4.3 (65.7)	193 (120)	10.2	N/A
aatomatio		18-inch	116	5.0 (56.5)	4.1 (68.9)	4.4 (64.2)	(120)		
		16-inch	114	5.6 (50.4)	3.6 (78.5)	4.4 (64.2)	210		
2.0 EcoBlue 6-speed manual	150	17-inch	115	5.6 (50.4)	3.6 (78.5)	4.4 (64.2)	210 (130)	8.5	8.4
		18-inch	116	5.6 (50.4)	3.7 (76.3)	4.5 (62.7)	(100)		
		16-inch	114	5.3 (53.3)	3.9 (72.4)	4.4 (64.2)	007		
2.0 EcoBlue 8-speed automatic	150	17-inch	117	5.5 (51.4)	4.0 (70.6)	4.5 (62.7)	207 (129)	9.3	N/A
automatic		18-inch	121	5.6 (50.4)	4.1 (68.9)	4.6 (61.4)	()		

Focus wagon					el consump ′100 km (mp		P	Performance		
Petrol engines	Power PS	Wheel size	CO₂ g/km	Urban	Extra Urban	Combined	Max speed km/h (mph)	0-100 km/h (0-62 mph) sec	50-100 km/h (31-62 mph) sec*	
1.0 EcoBoost 6-speed manual	85	16-inch	111	6.0 (47.1)	4.3 (65.7)	4.9 (57.6)	175 (109)	13.9	12.4	
1.0 EcoBoost 6-speed	100	16-inch**	108	5.9 (47.9)	4.1 (68.9)	4.8 (58.8)	184	12.5	12.4	
manual	100	17-inch	112	6.0 (47.1)	4.3 (65.7)	4.9 (57.6)	(114)	12.0	12.4	
	125	16-inch	108	5.9 (47.9)	4.2 (67.2)	4.8 (58.8)	100			
1.0 EcoBoost 6-speed manual	120	17-inch	112	6.0 (47.1)	4.3 (65.7)	4.9 (57.6)	198 (123)	10.3	10.3	
		18-inch	115	6.2 (45.6)	4.5 (62.7)	5.1 (55.4)	(120)			
10 FeeDeest 9 speed		16-inch	130	7.3 (38.7)	4.9 (57.6)	5.8 (48.7)	102	11.4		
1.0 EcoBoost 8-speed automatic	125	17-inch	132	7.4 (38.2)	5.0 (56.5)	5.9 (47.9)	193 (120)		N/A	
		18-inch	135	7.5 (37.7)	5.1 (55.4)	6.0 (47.1)	()			
1 E EcoDoost 6 anood		16-inch	125	7.0 (40.3)	4.7 (60.1)	5.5 (51.4)	208			
1.5 EcoBoost 6-speed manual	150	17-inch	127	7.1 (39.8)	4.7 (60.1)	5.6 (50.4)	208 (129)	9.0	8.9	
		18-inch	129	7.2 (39.2)	4.8 (58.8)	5.7 (49.5)	(,			
1 E EcoDoost 9 aroud		16-inch	134	7.6 (37.2)	5.0 (56.5)	5.9 (47.9)	206			
1.5 EcoBoost 8-speed automatic	150	17-inch	136	7.7 (36.7)	5.0 (56.5)	6.0 (47.1)	206 (128)	9.1	N/A	
		18-inch	138	7.8 (36.2)	5.2 (54.3)	6.2 (45.6)	()			
1.5 EcoBoost 6-speed	182	17-inch	127	7.1 (39.8)	4.7 (60.1)	5.6 (50.4)	220	8.5	8.6	
manual		18-inch	129	7.2 (39.2)	4.8 (58.8)	5.7 (49.5)	(137)	0.5	0.0	

Focus wagon				Fuel consumption	Performance
-------------	--	--	--	------------------	-------------

				۱/	100 km (mp	g)			
Diesel engines	Power PS	Wheel size	CO₂ g/km	Urban	Extra Urban	Combined	Max speed km/h (mph)	0-100 km/h (0-62 mph) sec	50-100 km/h (31-62 mph) sec*
		16-inch**	96	4.0 (70.6)	3.5 (80.7)	3.6 (78.5)	101		
1.5 EcoBlue 6-speed manual		16-inch	97	4.0 (70.6)	3.5 (80.7)	3.7 (76.3)	181 (112)	11.8	11.3
manaal		17-inch	100	4.1 (68.9)	3.7 (76.3)	3.8 (74.3)	()		
		16-inch	98	4.1 (68.9)	3.5 (80.7)	3.7 (76.3)		10.3	
1.5 EcoBlue 6-speed manual	120	17-inch	101	4.2 (67.2)	3.6 (78.5)	3.8 (74.3)	194 (120)		10.7
manaal		18-inch	104	4.3 (65.7)	3.7 (76.3)	3.9 (72.4)			
		16-inch	117	5.0 (56.5)	4.2 (67.2)	4.5 (62.7)	101		
1.5 EcoBlue 8-speed automatic	120	17-inch	120	5.1 (55.4)	4.3 (65.7)	4.6 (61.4)	191 (119)	10.5	N/A
		18-inch	123	5.2 (54.3)	4.4 (64.2)	4.7 (60.1)			
		16-inch	117	5.7 (49.5)	3.8 (74.3)	4.5 (62.7)			
2.0 EcoBlue 6-speed manual	150	17-inch	118	5.7 (49.5)	3.8 (74.3)	4.6 (61.4)	208 (129)	8.7	8.7
manaa		18-inch	119	5.7 (49.5)	3.9 (72.4)	4.6 (61.4)	(120)		
		16-inch	116	5.3 (53.3)	3.9 (72.4)	4.4 (64.2)	005		
2.0 EcoBlue 8-speed automatic	150	17-inch	119	5.5 (51.4)	4.1 (68.9)	4.6 (61.4)	205 (127)	9.5	N/A
		18-inch	122	5.6 (50.4)	4.2 (67.2)	4.7 (60.1)			

\* In 4th gear \*\* Low rolling resistance tyre

# WEIGHTS AND DIMENSIONS

## Weights

Focus 5-door							
	Kerb weight (kg) <sup>#</sup>	Gross Vehicle Mass (kg)	Gross Train Mass (kg)	Max. Towable Mass (braked) (kg)	Max. Towable Mass (unbraked) (kg)	Nose weight (kg)	Roof Ioad (kg)
1.0 EcoBoost 85 PS 6-speed manual	1322	1855	2955	1100	660	90	75
1.0 EcoBoost 100 PS 6-speed manual	1322	1855	2955	1100	660	90	75
1.0 EcoBoost 125 PS 6-speed manual	1322	1855	2955	1100	660	90	75
1.0 EcoBoost 125 PS 8-speed automatic	1371	1905	3205	1300	685	90	75
1.5 EcoBoost 150 PS 6-speed manual	1369	1890	3390	1500	680	90	75

1.5 EcoBoost 150 PS 8-speed automatic	1404	1905	3405	1500	700	75	75
1.5 EcoBoost 182 PS 6-speed manual	1369	1890	3590	1700	680	90	75
1.5 EcoBlue 95 PS 6-speed manual	1363	1895	3095	1200	680	90	75
1.5 EcoBlue 120 PS 6-speed manual	1363	1895	3295	1400	680	90	75
1.5 EcoBlue 120 PS 8-speed automatic	1394	1910	3310	1400	695	80	75
2.0 EcoBlue 150 PS 6-speed manual	1493	2020	3820	1800	745	90	75
2.0 EcoBlue 150 PS 8-speed automatic	1518	2045	3645	1600	750	90	75

Focus wagon							
	Kerb weight (kg) <sup>#</sup>	Gross Vehicle Mass (kg)	Gross Train Mass (kg)	Max. Towable Mass (braked) (kg)	Max. Towable Mass (unbraked) (kg)	Nose weight (kg)	Roof Ioad (kg)
1.0 EcoBoost 85 PS 6-speed manual	1383	1925	2925	1000	690	90	75
1.0 EcoBoost 100 PS 6-speed manual	1383	1925	2925	1000	690	90	75
1.0 EcoBoost 125 PS 6-speed manual	1383	1925	2925	1000	690	90	75
1.0 EcoBoost 125 PS 8-speed automatic	1431	1970	3270	1300	715	90	75
1.5 EcoBoost 150 PS 6-speed manual	1408	1950	3450	1500	700	90	75
1.5 EcoBoost 150 PS 8-speed automatic	1445	1980	3480	1500	720	90	75
1.5 EcoBoost 182 PS 6-speed manual	1408	1950	3650	1700	700	90	75
1.5 EcoBlue 95 PS 6-speed manual	1413	1955	3155	1200	705	80	75
1.5 EcoBlue 120 PS 6-speed manual	1413	1955	3355	1400	705	80	75
1.5 EcoBlue 120 PS 8-speed automatic	1454	1995	3395	1400	725	90	75
2.0 EcoBlue 150 PS 6-speed manual	1553	2080	3880	1800	750	90	75
2.0 EcoBlue 150 PS 8-speed automatic	1559	2105	3705	1600	750	90	75

<sup>#</sup>Represents the lightest kerbweight assuming driver at 75 kg, full fluid levels and 90 per cent fuel levels, subject to manufacturing tolerances and options, etc., fitted. Weights represent base model specification.

Towing limits quoted represent the maximum towing ability of the vehicle at its Gross Vehicle Mass to restart on a 12 per cent gradient at sea level. The performance and economy of all models will be reduced when used for towing. Gross Train Mass includes trailer weight.

## Dimensions

Dimensions (mm)	Focus 5-door	Focus Wagon		
Exterior				
Overall length	4378	4668		
Overall width with/without/folded mirrors	1979/1825/1848	1979/1825/1848		
Overall height (including antenna)	1471	1494		
Wheelbase	2700	2700		
Front track	1572	1572		
Rear track	1553	1566		
Front overhang	909	909		
Rear overhang	769	1059		
Min ground clearance (unloaded)	135	134		
Min ground clearance (loaded)	112	115		
Interior				
Front headroom	987	987		
Front max legroom	1109	1109		
Front shoulder room	1421	1421		
Front hip room	1364	1364		
Rear headroom	965	1008		
Rear legroom	918	918		
Rear shoulder room	1395	1395		
Rear hip room	1325	1325		
Luggage capacity (litres) <sup>‡</sup>				
5-seat mode, laden to package tray (with tyre repair kit)	375	608		
2-seat mode, laden to roof (with tyre repair kit)	1354	1653		
Luggage compartment dimensions (mm)				
Load length at floor to 1 <sup>st</sup> row (tyre repair kit)	1624	1835		
Load length at floor to 2nd row (tyre repair kit)	844	1047		
Load width between wheelhouses	1016	1150		
Load opening width (max)	1018	1051		
Load opening width (floor)	998	1078		
Load opening height	613	702		
Lift-over height (kerb)	680	625		
Fuel tank capacity (litres)				
Petrol/Diesel	52/47	52/47		

‡ Measured in accordance with ISO 3832. Dimensions may vary dependent on the model and equipment fitted. Dimensions represent base model specification.

## **DRIVER ASSISTANCE TECHNOLOGIES**

Active Park Assist 2 with Park-Out Assist
Adaptive Cruise Control with Stop & Go, Speed Sign Recognition and Lane-Centring
Adaptive Front Lighting System with Predictive curve light and Sign-based light
Adjustable Speed Limiter
Auto High Beam
Blind Spot Information System
Cross Traffic Alert with Active Braking
Distance Indication
Driver Alert
Evasive Steering Assist
Forward Collision Warning
Front and Rear Park Aid
Glare-free high beam
Head-up display
Hill Launch Assist
Intelligent Speed Limiter
Lane Keeping Aid
Lane Keeping Alert
Post-Collision Braking
Pre-Collision Assist with Pedestrian and Cyclist Detection
Rear wide-view camera
Traffic Sign Recognition
Wrong Way Alert

## **COMFORT AND CONVENIENCE**

B&O PLAY premium audio
Easy Fold Seats
Electric parking brake
FordPass Connect onboard modem
Hands-free tailgate
Heated steering wheel
Openable panoramic roof
Rotary Gear Shift Dial
SYNC 3 with 8-inch touchscreen
Wireless charging pad

# **STEERING**

System	Rack and pinion with column-mounted Electronic Power Assisted Steering module
Ratio	14.3:1
Turning circle (m) kerb-to-kerb	11.0 (16-/17-inch tyres) 11.6 (18-inch tyres)

# **CHASSIS**

Front suspension	Independent MacPherson struts with offset coil spring over gas filled twin-tube damper units and lower L-arms with optimised front rubber bushings and rear rubber bushings (or hydro-bush on selected powertrains) mounted on separate reinforced cross-member sub- frame, anti-roll bar.
Rear suspension	Twist-beam geometry with force vectoring springs. Mono-tube rear damper with optimised dual path body mounts
Rear suspension (wagon and selected 5- door powertrains)	Short-long-arm, multi-link independent geometry with isolated subframe. Unique geometry for wagon models. Twin-tube rear damper with optimised dual path body mounts. Unique dampers for wagon models. Optional Continuously Controlled Damping

## **BRAKES**

	Front	Rear		
Braking	Hydraulically operated dual-cir	Hydraulically operated dual-circuit system with diagonal		
	distribution. Vented front discs	distribution. Vented front discs. Solid rear discs. Electronic		
	four-channel anti-lock braking system (ABS) with electronic brake-force distribution (EBD), Electronic Stability Program (ESP) and Emergency Brake Assist (EBA). Autonomous			
	emergency braking (AEB) as part of Pre-Collision Assist with			
	Pedestrian Detection. Electric Brake Booster for selected			
	models			
Disc dimensions (mm)	Ø282 x 27 or Ø308 x 27	Ø271 x 12 or Ø302 x 12		
	depending on vehicle	depending on vehicle		
	configuration	configuration		
Piston dimensions (mm)	Ø57	Ø36 or Ø38 depending on vehicle configuration		

## WHEELS & TYRES

6.5 x 16-inch with 195/65 R16
6.5 x 16-inch with 205/60 R16
7 x 17-inch with 215/50 R17
8 x 18-inch with 235/40 R18

## **AERODYNAMICS**

Model	Cd
Focus 5-dr	0.273
Focus wagon	0.284

## PETROL ENGINES

		1.0-litre EcoBoost (85, 100, 125 PS)			
Туре		In-line three cylinder turbo petrol, Ti-VCT, transverse			nsverse
Displacement	cm <sup>3</sup>			99	
Bore	Mm		71	.9	
Stroke	Mm		82	2.0	
Compression ratio			10.	5:1	
Max power	PS (kW)	85 (63)	100 (74)	12	5 (92)
	at rpm	4000-6000	4500-6000		5000
Max torque	Nm	170	170		) overboost)
	at rpm	1400-3500	1400-4000	140	0-4500
Valve gear		DOHC with 4 va	alves per cylinder, tv	vin independent va	riable cam timing
Cylinders			3 in-line, cylinder dea	activation technolog	gy
Cylinder head			Cast alu	uminium	-
Cylinder block			Cast	iron	
Camshaft			Chain drive with h	udraulia tanaianan	
drive			Chain drive with h	ydraulic tensioner	
Crankshaft		Cast iron, 6 counterweights, 4 main bearings			
Engine		Bosch MED17 with CAN-Bus and individual cylinder knock control. FGEC			
management			software		
Fuel injection		High pr	High pressure direct fuel injection with 5 hole injectors		
Emission level		Euro 6d-TEMP			
Emission					
control		Rapid light-off catalyst, gasoline particulate filter			
Turbocharger		Continental radial-axial (RAAX) turbocharger			
Lubrication		Electronically controlled variable displacement oil pump for improved fuel			
system		economy			
System capacity with filter	Litres	4.6			
Cooling system		Split cooling system with 2 thermostats. Cam driven water pump for reduced power consumption			
System capacity incl heater	Litres	6.0 manual/6.4 auto			
Transmission					8-speed automatic
Gear ratios		6th 0.634 5th 0.757 4th 0.943 3rd 1.276 2nd 1.958 1st 3.417 R 3.895	6th 0.634 5th 0.757 4th 0.943 3rd 1.276 2nd 1.958 1st 3.417 R 3.895	6th 0.634 5th 0.757 4th 0.943 3rd 1.276 2nd 1.958 1st 3.417 R 3.895	NA
		FDR 4.353	FDR 4.353	FDR 4.353	

		1.5-litre EcoBoost			
Туре		(150, 182 PS) In-line three cylinder turbo petrol, Ti-VCT, transverse			
Displacement	cm <sup>3</sup>				
Bore	Mm	84.0			
Stroke	Mm	90.0			
Compression					
ratio			11.0	:1	
Max power	PS (kW)		(110)	182 (134)	
	at rpm		000	6000	
Max torque	Nm		40	240	
	at rpm	-	300	1600	
Valve gear				n independent variable cam timing	
Cylinders		3	3 in-line, cylinder dea		
Cylinder head			Cast alur		
Cylinder block			Cast alur	ninium	
Camshaft drive			Chain driven with h	ydraulic tensioner	
Crankshaft		Ca	st iron, 6 counterweig	ghts, 4 main bearings	
Engine		Bosch MG1CS0	Bosch MG1CS016 with CAN-Bus and individual cylinder knock control.		
management			FGEC software		
Fuel injection		3 high-pressure direct fuel injection, 6 hole injectors (DI) plus 3 low-pressure port injectors (PFI)			
Emission level		Euro 6d-TEMP			
Emission		Der	al lanks of sately at a	Bar	
control		Rapid light-off catalyst, gasoline particulate filter			
Turbocharger		Continental radial-axial (RAAX) turbocharger			
Lubrication		Two-stage variable displacement oil pump			
system System	Litres				
capacity with	Lines	5.25			
Cooling system		Single thermostat			
System capacity incl heater	Litres	6.1 manual/6.5 auto			
Transmission		6-speed manual	8-speed automatic	6-speed manual	
Gear ratios		6th 0.651		6th 0.651	
		5th 0.775		5th 0.775	
		4th 0.971		4th 0.971	
		3rd 1.290		3rd 1.290	
		2nd 1.952	N/A		
			11//4	2nd 1.952	
		1st 3.583		1st 3.583	
		Reverse 3.333		Reverse 3.333	
		FDR1: 4.056		FDR1: 4.313	
		FDR2: 4.563		FDR2: 4.929	

For news releases, related materials, photos and video, visit <u>www.fordmedia.eu</u> or <u>www.media.ford.com</u>. Follow <u>www.twitter.com/FordEu</u> or <u>www.youtube.com/fordofeurope</u>

## **DIESEL ENGINES**

		1.5-litre EcoBlue		
		(95, 120 PS)		
Туре		In-line four cylinder turbo diesel, transverse		
Displacement	cm <sup>3</sup>	1500		
Bore	Mm		75.0	
Stroke	Mm		84.8	
Compression			16.4:1	
ratio	50			
Max power	PS (kW)	95 (70)		(88)
	at rpm	3600		600
Max torque	Nm	300		00
	at rpm	1750-2000		-2250
Valve gear		DC	HC with 4 valves per cylin	der
Cylinders			4 in-line	
Cylinder head			Cast aluminium	
Cylinder block			Cast aluminium	
Camshaft drive			einforced primary drive be	
Crankshaft		Steel forging, 4 counter-weights, 5 main bearings		
Engine			Bosch FDEC	
management				
Fuel injection		Common rail direct fuel injection; 2000 bar injection pressure; 8-hole injectors		
Emission level		Euro 6d-TEMP		
Emission		High- and low-pressure exhaust gas recirculation; water-air charge cooling;		
control		Twin lean NOx trap		
Turbocharger		Low-inertia variable geometry turbocharger with electronic control		
Lubrication		Pressure-fed lubrication system with full flow oil filter, variable displacement		
system		oil pump		
System	litres			
capacity with		3.8		
filter				
Cooling system	litroo	Water pump with electrically switchable thermostat		
System capacity	litres	6.7 manual/7.3 auto		
Transmission		6-speed manual 8-speed automatic		
Gear ratios		6th 0.578	6th 0.578	
Gearralios		5th 0.690	5th 0.690	
		4th 0.868	4th 0.868	
		3rd 1.194	3rd 1.194	
		2nd 1.952	2nd 1.952	N/A
		1st 3.727	1st 3.727	
		Reverse 3.455	Reverse 3.455	
		FDR1: 3.316	FDR1: 3.526	
		FDR2: 3.706	FDR2: 3.941	

		2.0-litre EcoBlue		
		(150 PS)		
Туре		Inline four cylinder turbo diesel, transverse		
Displacement	cm <sup>3</sup>	1996		
Bore	Mm	84.0		
Stroke	Mm	90	0.0	
Compression ratio		15.	8:1	
Max power	PS (kW)	150	(110)	
	at rpm	35	00	
Max torque	Nm		70	
	at rpm		-2500	
Valve gear			lves per cylinder	
Cylinders			line	
Cylinder head		Cast alı	uminium	
Cylinder block		Cast	t iron	
Camshaft drive		Low-friction belt-in-oil	with dynamic tensioner	
Crankshaft			weights, 5 main bearings	
Engine management		Ford Common Rail Diesel Engine Management System		
Fuel injection		Common rail direct fuel injection; 2200 bar injection pressure;		
-		8-hole piezo-electric injectors		
Emission level		Euro 6d-TEMP		
Emission control		High- and low-pressure exhaust gas recirculation; water-air charge cooling; selective catalytic reduction after treatment		
Turbocharger		Low-inertia variable geometry turbocharger with electronic control		
Lubrication system		Pressure-fed lubrication system with full flow oil filter, variable displacement oil pump		
System capacity with filter	litres	7.25		
Cooling system		Engine driven water pump with thermostat control		
System capacity	litres	7.7 manual (8.8 manual inc. fuel operated heater)/8.3 auto		
Transmission		6-speed manual	8-speed automatic	
Gear ratios		6th 0.737		
		5th 0.886		
		4th 0.816		
		3rd 1.156		
		2nd 1.864	N/A	
			IN/A	
		1st 3.583		
		Reverse 1.423		
		FDR1: 3.688		
		FDR 2: 2.682		

For news releases, related materials, photos and video, visit <u>www.fordmedia.eu</u> or <u>www.media.ford.com</u>. Follow <u>www.twitter.com/FordEu</u> or <u>www.youtube.com/fordofeurope</u>

Note: The data information in this press release reflects preliminary specifications and was correct at the time of going to print. However, Ford policy is one of continuous product improvement. The right is reserved to change these details at any time.

Note: The declared Fuel/Energy Consumptions,  $CO_2$  emissions and electric range are measured according to the technical requirements and specifications of the European Regulations (EC) 715/2007 and (EC) 692/2008 as last amended. Fuel consumption and  $CO_2$  emissions are specified for a vehicle variant and not for a single car. The applied standard test procedure enables comparison between different vehicle types and different manufacturers. In addition to the fuel-efficiency of a car, driving behaviour as well as other non-technical factors play a role in determining a car's fuel/energy consumption,  $CO_2$  emissions and electric range.  $CO_2$  is the main greenhouse gas responsible for global warming.

From 1 September 2017, certain new vehicles will be type-approved using the World Harmonised Light Vehicle Test Procedure (WLTP) according (EU) 2017/1151 as last amended, which is a new, more realistic test procedure for measuring fuel consumption and  $CO_2$  emissions. From 1 September 2018 the WLTP will fully replace the New European Drive Cycle (NEDC), which is the current test procedure. During NEDC Phase-out, WLTP fuel consumption and  $CO_2$  emissions are being correlated back to NEDC. There will be some variance to the previous fuel economy and emissions as some elements of the tests have altered i.e., the same car might have different fuel consumption and  $CO_2$  emissions.

#### About Ford Motor Company

Ford Motor Company is a global company based in Dearborn, Michigan. The company designs, manufactures, markets and services a full line of Ford cars, trucks, SUVs, electrified vehicles and Lincoln luxury vehicles, provides financial services through Ford Motor Credit Company and is pursuing leadership positions in electrification, autonomous vehicles and mobility solutions. Ford employs approximately 202,000 people worldwide. For more information regarding Ford, its products and Ford Motor Credit Company, please visit <u>www.corporate.ford.com</u>.

**Ford of Europe** is responsible for producing, selling and servicing Ford brand vehicles in 50 individual markets and employs approximately 54,000 employees at its wholly owned facilities and approximately 69,000 people when joint ventures and unconsolidated businesses are included. In addition to Ford Motor Credit Company, Ford Europe operations include Ford Customer Service Division and 24 manufacturing facilities (16 wholly owned or consolidated joint venture facilities and eight unconsolidated joint venture facilities). The first Ford cars were shipped to Europe in 1903 – the same year Ford Motor Company was founded. European production started in 1911.

Contact: Finn Thomasen Ford of Europe +44 (0) 1268 401 908 fthomas3@ford.com